



[www.tabe-hammers.com](http://www.tabe-hammers.com)



MARTILLOS  
HIDRÁULICOS

HYDRAULIC  
BREAKERS

BRISE ROCHES  
HYDRAULIQUES

MARTILLOS HIDRÁULICOS  
HYDRAULIC BREAKERS  
BRISE ROCHES HYDRAULIQUES



Sistema Pare  
Pare System  
Non-contact strike system



Circuito engrase automático  
Automatic lubrication  
Graissage aut.



Trabajos submarinos  
Under-water excavation  
Travaux sous-l'eau



Cambio de frecuencia  
Stroke switching  
Changement de vitesse



Protección latiguillos  
Hose-protection  
Protection de flexibles

S - serie  
O - option

	kg	t.	mm	l/min.	Bar	min.	D(mm)	L(mm)	kg						$\beta$ system
<b>AGB-95</b>	105	0,8-3,5	1046	20-35	80-100	650-1200	45	420	7,8	-	-	-	-	-	-
<b>AGB-175</b>	170	2,5-4,5	1060	40-50	80-90	1000-1200	50	450	6	O	-	O	-	-	-
<b>AGB-275</b>	275	3,5-5,5	1220	60-70	80-90	850-1000	65	610	15	S	-	O	-	-	-
<b>AGB-375</b>	340	4,5-7	1300	65-75	130-135	800-950	65	610	15	S	-	O	-	-	-
<b>AGB-475BC</b>	410	6-10	1338	70-80	140-150	850-975	84	700	26	S	-	O	-	-	-
<b>AGB-575</b>	600	8-15	1650	90-125	130-140	700-1000	90	850	39	S	-	-	-	-	-
<b>AGB-10B</b>	950	10-16	1870	85-110	150-175	450-590	105	1000	61	S	S	S	O	S	-
<b>AGB-12</b>	1300	15-23	2100	90-120	150-170	450-700	120	1100	90	O	S	O	O	S	-
<b>AGB-15</b>	1470	19-25	2265	120-145	150-180	400-800	135	1100	112	S	S	S	S	S	-
<b>AGB-18</b>	1950	24-28	2390	130-155	160-190	450-750	135	1100	112	S	S	S	S	S	O
<b>AGB-20STA</b>	2300	25-35	2485	175-220	160-190	350-600	150	1320	166	S	S	S	S	S	O
<b>AGB-30STA</b>	3300	30-50	2815	205-245	160-190	300-550	165	1525	205	S	S	S	S	S	O
<b>AGB-40</b>	4850	45-70	3025	250-340	160-190	250-340	210	1600	275	S	S	S	S	S	O

El fabricante se reserva el derecho de cambiar estas características técnicas sin previo aviso.  
Manufacturer has the right to change these technical features without previous notice.  
Le fabricant se réserve le droit de modifier les données techniques sans preavuu.

Dealer:



VERKOOP & VERHUUR  
ONBEMAND MATERIEEL

078 64 52 276

WWW.AAMACHINES.NL



www.tube-hammers.com