

Excavator Forestry Mulchers

Tough Design for Wood Mulching

Blades are engineered to shatter woods and designed to turn directions of blades to use in double.

Double-time use

One-direction Turning for safety

High Speed RPM



RBM Series

Model		Specifications			
		RBM 1200-5	RBM 1200-8	RBM 1200-14	
Op. Weight	kg	350(stn) / 420(h.rtn)	380(stn) / 450(h.rtn)	380(stn) / 470(h.rtn)	
Operation Oil Pressure	bar	200~250	200~250	200~250	
Operation Oil Flow	lpm	45~54	60~72	92~109	
Rotation	rpm	3500~4500	3500~4500	3500~4500	
Max. Cutting Dia.	mm	1 ~ 200	1 ~ 200	1 ~ 200	
Motor Capacity	cc	27	36	47	
No. of Blades	pieces	28	28	28	
Excavator Weight	ton	5~6.5	8~10	14~16	
Dimensions	Length	mm	1450	1450	
	Height	mm	920(std)/1020(h.rtn)	950(stn)/1050(h.rtn)	1020(stn)/1120(h.rtn)
	Width	mm	620	620	620
Pulley - Upper	inch	9.5	9.5	9	
Pulley - Lower	inch	5	5	5.5	
Belt	inch	B52	B52	B52	
Rotor	Total Length	mm	1450	1450	1450
	Cutting Length	mm	1200	1200	1200
	Diameter	mm	168	168	168
Motor Type		Piston	Piston	Piston	