Main Technical Parameters of Telescopic Wheel Loader Model ZL10

	Item	Parameters
Performance	1. Rated Load	1000 kg
	2. Total Weight	3600 kg
	3. Rated Bucket Capacity	0.5 m ³
	4. Bucket Width	1600mm
	5. Max. Breakout Force	39 KN
	6. Max. Gradeability	30°
	7. Max. Dumping Height (fully raised height to the pin)	4000 mm
	8. Raising Time	< 5.0s
	9. Overall Dimensions (L x W x H)	4350*1790*2720 mm
	10. Min. Turning Radius	4500 mm
Engine	11. Model	CHANGCHAI ZN490B
	12. Type	Four-cylinder, Inline, Water-cooled, Four-stroke Diesel Engine
	13. Rated Power	39 kW
	14. Rated Speed	2400rpm
	15. Engine Starting Mode	Electric
Transmission System	16. Hydraulic Torque Converter	ZL265 Integrated Hydraulic Torque Converter
	17. Gear Shift	1 Forward, 1 Reverse, 1 High Speed, 1 Low Speed
	18. Max. Speed	25 km/h
Drive Axle	19. Wheel Tread	1500 mm
	20. Wheel Base	2400 mm
Drive	21. Mode	4-wheel Drive
Brake System	22. Service Brake	Foot Pedal Vacuum Assisted Hydraulic, Expansion-shoe Brake on 4 Wheels
	23. Parking Brake	Hand Lever Flexible Shaft Controlled Disc Brake
Tyre	24. Type Specification	12-16.5-14PR
	25. Front Tyre Pressure	0.40 Mpa
	26. Rear Tyre Pressure	0.35 Mpa
Photo	Promising co.cn	



Standard Configuration:



Enclosed Cabin



Enclosed Cabin (Newly Designed)



Digital Radio + MP3 Player



Electric Fan



Heater



Adjustable Suspension Seat



Emergency Hammer



Fire Extinguisher



Rotating Beacon



Mechanical Joystick



Mechanical Gear Shift Lever (Automatic Transmission)



Hydraulic Quick Coupler/Quick Hitch /Quick Attach

Note:

- 1. The technical specifications are for standard models only.
- 2. Other optional accessories and requirements are available upon request.
- 3. All photos are for reference only. Machines shown may include optional parts.
- 4. All specifications and design characteristics are subject to change without prior notice.
- 5. For all available loader attachments, please refer to our Loader Attachments Catalogue.

QINGDAO PROMISING INTERNATIONAL CO., LTD.

Optionally Parts and Functions:



Canopy



Open Cabin



FOPS/ROPS



Tilting Cabin (up to 30° for Easy Maintenance)



Hydraulic Joystick Control + Quick Hitch Lever + Armrest



Air Conditioner (Some Models Only)



Color Coded Electronic Gear Shift Button on Joystick



Gear Shift Lever with Electronic Control



Headlight Cover



Reversing Camera



Euro Standard Quick Coupler



Skid Steer (Bobcat) Quick Coupler/Quick Attach/Quick Hitch



Number Plate

Note:

Equipped with hydraulic quick coupler, your wheel loader can be easily and conveniently switched from one attachment to another to save your time and labor. Equipped with skid steer (Bobcat) quick coupler or Euro Standard quick coupler, you can use all your existing attachments with our wheel loader.