



NOT FOR HIGHWAY SERVICE

SAFETY WARNING
DO NOT DRIVE WITH EXPOSED
WIRE REINFORCEMENT
ONLY SPECIALLY TRAINED PERSONS SHOULD MOUNT TIRES
NEVER EXCEED 1500 PSI OR OTHER SEALING BEADS
NEVER WELD THE RIM WITHOUT FIRST REMOVING
THE TIRE
ALWAYS FOLLOW INSTRUCTIONS IN EQUIPMENT
OWNER'S MANUAL AND PROPER MOUNTING AND
OPERATING PROCEDURES

NGT H O

24x13.00-12

AS20-1

6 P.B.

MADE IN JAPAN

235/40R17 (235/40R17) (235/40R17) (235/40R17)
235/40R17 (235/40R17) (235/40R17) (235/40R17)
235/40R17 (235/40R17) (235/40R17) (235/40R17)
235/40R17 (235/40R17) (235/40R17) (235/40R17)





MADE IN JAPAN

OHTSU

VM X4915

TUBELESS

96 P.R.

20x8.00-10

SAFETY WARNING:
DO NOT DRIVE WITH TIRE AT FULL LOAD
DO NOT DRIVE AT HIGH SPEED (55 MPH)
DO NOT DRIVE AT HIGH SPEED (55 MPH) WHEN SEATING DECKS--
DO NOT DRIVE AT HIGH SPEED (55 MPH) WHEN SEATING DECKS--
DO NOT DRIVE AT HIGH SPEED (55 MPH) WHEN SEATING DECKS--